

ZCKE05

limit switch head ZCKE - without lever left and right actuation



Main

Range of product	OsiSense XC
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Rotary head
Product compatibility	XCKJ
Associated lever	ZCKY91 ZCKY52 ZCKY53 ZCKY11 ZCKY13 ZCKY43 ZCKY51 ZCKY14 ZCKY81 ZCKY41 ZCKY59
Associated body	ZCKJD37H7 ZCKJ5H29 ZCKJ8H7 ZCKJ1H29 ZCKJ8 ZCKJ7 ZCKJ41 ZCKJ6H29 ZCKJ11H29 ZCKJ41H29 ZCKJ11H7 ZCKJD35H7 ZCKJD31H7 ZCKJ9H29 ZCKJD31H29 ZCKJ21 ZCKJD39H7 ZCKJ9H7

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

ZCKJ4H29
 ZCKJD35H29
 ZCKJ6
 ZCKJ11
 ZCKJ5
 ZCKJ7H29
 ZCKJ1H7
 ZCKJ7H7
 ZCKJ9
 ZCKJ8H29
 ZCKJ6H7
 ZCKJ4104H29
 ZCKJD31
 ZCKJ4104H7
 ZCKJ5H7
 ZCKJ2H7
 ZCKJ404H29
 ZCKJD37H29
 ZCKJ4
 ZCKJ21H7
 ZCKJ1
 ZCKJ2H29
 ZCKJD39H29
 ZCKJD37
 ZCKJ2
 ZCKJD35
 ZCKJ41H7
 ZCKJ404
 ZCKJD39
 ZCKJ4104
 ZCKJ21H29
 ZCKJ4H7
 ZCKJ404H7

Movement of operating head	Rotary
Type of operator	Without operating lever spring return
Type of approach	Lateral approach, 1 or 2 programmable direction

Complementary

Switch actuation	From left and/or right CW and/or CCW
Positive opening	With
Head material	Metal

Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Environmental characteristic	Standard environment

Packing Units

Package 1 Weight	0.167 kg
------------------	----------

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------