

Cutting-off wheel

A 24 R SUPRA



Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Aluminium oxide
Bond	■■■■■□□
Aggression	■■■■■□□
Service life	■■■■■□□

Product benefit

Optimized combination for use on steel - Can be used on stainless steel - Good cutting properties

Application

Steel	●
Stainless steel	◐
Castings	◑

Target group

- Plant engineering
- Apparatus and container manufacturing
- Metal construction
- Locksmith's shop

Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
100 x 2,5 x 16		80 m/s	15300 rpm	25	13754
115 x 2,5 x 22,23		80 m/s	13300 rpm	25	231859
115 x 2,5 x 22,23		80 m/s	13300 rpm	25	231868
125 x 2,5 x 22,23		80 m/s	12200 rpm	25	13295
150 x 2,5 x 22,23		80 m/s	10200 rpm	25	6667
180 x 3 x 22,23		80 m/s	8500 rpm	25	231864
230 x 3 x 22,23		80 m/s	6600 rpm	25	231866
230 x 3 x 22,23		80 m/s	6600 rpm	25	231872

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

