

# Grinding disc

# A 24 R SUPRA



## Properties

|               |                                   |
|---------------|-----------------------------------|
| Bonding agent | Synthetic resin, fibre-reinforced |
| Type of grain | Aluminium oxide                   |
| Bond          | ■■■■■□□□                          |
| Aggression    | ■■■■■□□□                          |
| Service life  | ■■■■■□□□                          |

## Product benefit

With optimised recipe for use on steel - Also suitable for use on stainless steel - Large product range

## Application

|                 |   |
|-----------------|---|
| Steel           | ● |
| Stainless steel | ◐ |
| Castings        | ◑ |

## Applications

- Plant engineering
- Apparatus and container manufacturing
- Metal construction
- Locksmith's shop

| Diameter x Width<br>x Bore in mm | Form | Vmax m/s | Max.<br>RPM | Packing<br>unit/pcs. | Cat.<br>number |
|----------------------------------|------|----------|-------------|----------------------|----------------|
| 100 x 6 x 16                     |      | 80 m/s   | 15300 rpm   | 10                   | 6578           |
| 115 x 6 x 22,23                  |      | 80 m/s   | 13300 rpm   | 10                   | 13401          |
| 125 x 6 x 22,23                  |      | 80 m/s   | 12200 rpm   | 10                   | 13402          |
| 150 x 6 x 22,23                  |      | 80 m/s   | 10200 rpm   | 10                   | 13403          |
| 230 x 6 x 22,23                  |      | 80 m/s   | 6600 rpm    | 10                   | 13433          |

**Klingspor Schleifsysteme GmbH und Co. KG**

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

