

Product datasheet

Specifications



Occupancy sensor, ARGUS, single load - 360 degree

SAE-UE-MS-CSAWE

⚠ Discontinued on: 01 Dec 2024

⚠ To be discontinued

Main

Range	ARGUS
Product or component type	Occupancy sensor
Device application	Lighting
Load type	Halogen lamp <= 1000 VA Energy saving lamp <= 80 VA Incandescent lamp <= 2000 W Low voltage halogen lamp <= 1000 VA Fluorescent lamp 100 µF <= 900 VA

Complementary

Rated voltage	230 V +/- 10 % AC 50/60 Hz
Detection angle	360°
Presence detection area	PIR: 360°, 7 x 7 m
Device mounting	Flush Surface
Mounting support	Ceiling
Mounting height	2...3 m
Diameter	111 mm
Depth	66 mm

Environment

Electrical shock protection class	Class II
IP degree of protection	IP40 flush mounting IP44 surface mounting
Ambient air temperature for operation	0...45 °C indoor -20...45 °C outdoor
Standards	EN 60669-1 EN 60669-2-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.408 cm
Package 1 Width	11.811 cm
Package 1 Length	11.964 cm

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Weight	250.0 g
------------------	---------

Contractual warranty

Warranty (in months)	18
----------------------	----