



Main

Range of product	Acti 9
Product or component type	Overvoltage release
Device short name	IMSU
[Uc] control circuit voltage	230 V AC 50/60 Hz
Threshold tripping voltage	255 V 275 V 3...15 s 300 V 1...5 s 350 V 0.25...0.75 s 400 V 0.07...0.2 s
9 mm pitches	2

Complementary

Range compatibility	Acti 9 iC65 Acti 9 ARA Acti 9 iDPN Vig Acti 9 iID Acti 9 iSW-NA Acti 9 RCA Acti 9 iDPN (China version) Acti 9 iC60 double terminals miniature circuit breaker Acti 9 iC40
Local signalling	Action indicator
Mounting mode	Clip-on
Mounting support	DIN rail
Height	82.5 mm
Width	18 mm
Depth	68 mm
Colour	White
Connections - terminals	Clamp terminal - 1 cable(s) 0.5...4 mm ² - flexible Clamp terminal 1...6 mm ² - rigid

Wire stripping length	10 mm
Tightening torque	1 N.m
Compatibility code	IMSU

Environment

Standards	EN 50550
Quality labels	CE
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-35...70 °C
Ambient air temperature for storage	-40...85 °C

Packing Units

Package 1 Weight	80 g
Package 2 Weight	747 g
Package 3 Weight	6.694 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------