Product datasheet Characteristics

RUZC2M

Socket, mixed contact, 10 A, relay type RUMC2, screw connector, 250 V AC





Main

| Man | | |
|-------------------------------|--|----------------|
| Range of product | Harmony Relay | |
| Product or component type | Socket | Ť |
| Contact terminal arrangement | Mixed | |
| Product compatibility | Plug-in relay RUM with 2 C/O contact Plug-in relay RE48 with 2 C/O contact Plug-in relay RE48 with 1 C/O + 1 C/O contact | ability of the |
| Shape of pin | Cylindrical | <u> </u> |
| Device short name | RUZ | <u> </u> |
| Sale per indivisible quantity | 10 | |
| | | |

Complementary

| · · · · · · · · · · · · · · · · · | | |
|---|--|-----------|
| [lth] conventional free air thermal current | 10 A | Log pesi |
| [Ue] rated operational voltage | < 250 V | |
| Tightening torque | < 1 N.m for M3.5 screw(s) | + |
| Fixing mode | By screw (panel) Clip-on (35 mm symmetrical DIN rail) | or and is |
| Marking | CE | |
| Width | 38 mm | tg ii |
| Net weight | 0.054 kg | |
| | | |

Environment

| | | > |
|-------------------------|---|-----------------|
| Connections - terminals | Connector, 1 x 0.251 x 2.5 mm² (AWG 22AWG 14) flexible with cable end Connector, 2 x 0.252 x 1 mm² (AWG 22AWG 17) flexible with cable end Connector, 1 x 0.51 x 2.5 mm² (AWG 20AWG 14) solid without cable end Connector, 2 x 0.52 x 1.5 mm² (AWG 20AWG 16) solid without cable end | omentation is r |
| Standards | IEC 61984 | |
| Product certifications | UL | Ė |

| Ambient air temperature for storage | -4085 °C |
|---------------------------------------|---------------------------------|
| Ambient air temperature for operation | -4055 °C |
| IP degree of protection | IP20 conforming to EN/IEC 60529 |
| Dielectric strength | 2500 V |

Packing Units

| Unit Type of Package 1 | PCE | |
|------------------------------|-----------|--|
| Number of Units in Package 1 | 1 | |
| Package 1 Weight | 55 g | |
| Package 1 Height | 8 cm | |
| Package 1 width | 8 cm | |
| Package 1 Length | 13.7 cm | |
| Unit Type of Package 2 | BB1 | |
| Number of Units in Package 2 | 10 | |
| Package 2 Weight | 600 g | |
| Package 2 Height | 8.4 cm | |
| Package 2 width | 8.4 cm | |
| Package 2 Length | 14.4 cm | |
| Unit Type of Package 3 | S03 | |
| Number of Units in Package 3 | 200 | |
| Package 3 Weight | 11.327 kg | |
| Package 3 Height | 30 cm | |
| Package 3 width | 30 cm | |
| Package 3 Length | 40 cm | |

Offer Sustainability

| Sustainable offer status | Green Premium product | |
|----------------------------|---|--|
| REACh Regulation | REACh Declaration | |
| REACh free of SVHC | Yes | |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration | |
| Toxic heavy metal free | Yes | |
| Mercury free | Yes | |
| RoHS exemption information | Yes | |
| China RoHS Regulation | China RoHS declaration | |
| Environmental Disclosure | Product Environmental Profile | |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins | |

Contractual warranty

| Warranty | 18 months | |
|----------|-----------|--|

Product datasheet Dimensions Drawings

RUZC2M

Socket

8-Pin Socket





