Product datasheet Characteristics

VZ7

TeSys VARIO - auxiliary contact block - 1 NC early-break+1 NO late-make





Main

-	T.A.	
Range	TeSys	
Device short name	VZ	
Product or component type	Auxiliary contact block	
Performance level	High performance	
Contacts type and composition	1 NO + 1 NC	
Contact operation	Late-make 1 NO Early-break 1 NC	
Product compatibility	V2 V5 V02 V6 V1 V4 V01 V0 V3	
Network type	AC DC	
Network frequency	50/60 Hz	

Complementary

Mounting location	Right	- 6
[Ue] rated operational voltage	690 V AC 50/60 Hz	_ paper
[Uimp] rated impulse withstand voltage	8 kV	ot inte
[lth] conventional free air thermal current	12 A	l n si noite
[Ithe] conventional enclosed thermal current	10 A	- ocument
Mechanical durability	100000 cycles	his d
Electrical durability	30000 cycles DC-11	_F:-

100000 cycles AC-15

Connections - terminals	Screw clamp terminals 2 cable(s) 0.751.5 mm² - flexible - with cable end Screw clamp terminals 2 cable(s) 12.5 mm² - solid	
Tightening torque	0.7 N.m - on screw clamp terminals	
Height	65 mm	
Width	20 mm	
Depth	48.5 mm	
Net weight	0.05 kg	

Environment

Standards	IEC 60947-5
Product certifications	GL CSA UL
Protective treatment	TC
IP degree of protection	IP20 conforming to IEC 60529
Ambient air temperature for operation	-2050 °C
Fire resistance	960 °C conforming to IEC 60695-2-1

Packing Units

I acking office		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	54 g	
Package 1 Height	3.7 cm	
Package 1 width	5.5 cm	
Package 1 Length	9 cm	
Unit Type of Package 2	S02	
Number of Units in Package 2	69	
Package 2 Weight	4.035 kg	
Package 2 Height	15 cm	
Package 2 width	30 cm	
Package 2 Length	40 cm	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Environmental Disclosure	Product Environmental Profile	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
PVC free	Yes	
Halogen content performance	Halogen free product	

Contractual warranty

Warranty	18 months