



Main

| | |
|-------------------------------|-------------------------------------|
| Range of product | OsiSense XU |
| Series name | General purpose single mode |
| Electronic sensor type | Photo-electric sensor |
| Sensor name | XU2 |
| Sensor design | Cylindrical M18 |
| Detection system | Thru beam |
| Material | Metal |
| Line of sight type | Axial |
| Type of output signal | Discrete |
| Supply circuit type | AC/DC |
| Wiring technique | 2-wire |
| Discrete output function | 1 NO |
| Electrical connection | 1 male connector 1/2"20 UNF, 3 pins |
| Product specific application | - |
| Emission | Infrared thru beam |
| [Sn] nominal sensing distance | 15 m thru beam |

Complementary

| | |
|---------------------------|--|
| Enclosure material | Nickel plated brass |
| Lens material | PMMA |
| Maximum sensing distance | 20 m |
| Output type | Solid state |
| Add on output | Without |
| Status LED | 1 LED (yellow) for output state 1 LED (red) for instability |
| [Us] rated supply voltage | 24...240 V AC/DC |

| | |
|--------------------------|---|
| Supply voltage limits | 20...264 V AC/DC |
| Maximum residual current | 1.5 mA open state |
| Switching capacity in mA | 10...200 mA (to be used with 0.4 A quick-blow fuse in series with the load) |
| Switching frequency | <= 25 Hz |
| Maximum voltage drop | <6 V (closed state) |
| Maximum delay first up | 300 ms |
| Maximum delay response | 20 ms |
| Maximum delay recovery | 20 ms |
| Setting-up | Sensitivity adjustment |
| Diameter | 18 mm |
| Length | 95 mm |
| Net weight | 0.155 kg |
| Kit composition | Transmitter + receiver XU2M18MC230KT + XU2M18MA230KR |

Environment

| | |
|---------------------------------------|---|
| Product certifications | UL CE CSA |
| Ambient air temperature for operation | -25...55 °C |
| Ambient air temperature for storage | -40...70 °C |
| Vibration resistance | 7 gn, amplitude = +/- 1.5 mm (f = 10...55 Hz) conforming to IEC 60068-2-6 |
| Shock resistance | 30 gn (duration = 11 ms) conforming to IEC 60068-2-27 |
| IP degree of protection | IP67 conforming to IEC 60529 |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 162 g |
| Package 1 Height | 13 cm |
| Package 1 width | 9 cm |
| Package 1 Length | 4.2 cm |
| Unit Type of Package 2 | S01 |
| Number of Units in Package 2 | 11 |
| Package 2 Weight | 1.998 kg |
| Package 2 Height | 15 cm |
| Package 2 width | 15 cm |
| Package 2 Length | 40 cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|