Product datasheet Characteristics

ZCKD23

limit switch head ZCKD - steel roller lever plunger with protective boot





Main	
Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKD
Head type	Plunger head
Product compatibility	XCKM XCKL
Associated body	ZCKMD37H7 ZCKMD31H29 ZCKM6H29 ZCKM1H29 ZCKMD37H29 ZCKM8H7 ZCKL5H7 ZCKL5H7 ZCKL6 ZCKM6 ZCKLD39 ZCKL1 ZCKM1H7 ZCKL1 ZCKM5 ZCKM8H29 ZCKM8H29 ZCKLD39H7 ZCKL1H7 ZCKL1H7 ZCKLD39H7 ZCKL1H7 ZCKLD39H7

ZCKMD37

ZCKM7
ZCKLD37
ZCKMD39H7
ZCKM9H29
ZCKMD31
ZCKL5
ZCKL6H7
ZCKLD31H7
ZCKMD35
ZCKM7H29
ZCKM5H29
ZCKLD35H7

ZCKLD35H7 ZCKMD35H7 ZCKL8

ZCKM5H7 ZCKL7 ZCKLD31

ZCKLD31 ZCKL8H7 ZCKM7H7

Movement of operating head Rotary Linear

Type of operator Roller lever plunger spring return metal

Type of approach Lateral approach, 1 direction

Complementary

Switch actuation	By 30° cam
Positive opening	With
Head material	Plastic

Environment

Ambient air temperature for operation	-2570 °C
Ambient air temperature for storage	-4070 °C
Environmental characteristic	Standard environment

Packing Units

Package 1 Weight	0.096 kg	
Package 1 Height	0.330 dm	
Package 1 width	0.630 dm	
Package 1 Length	0.750 dm	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
Environmental Disclosure	Product Environmental Profile	

Contractual warranty

Warranty	18 months