



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Plunger head
Product compatibility	XCKJ
Associated body	ZCKJ8 ZCKJ9H29 ZCKJ6H29 ZCKJ41H29 ZCKJD37 ZCKJD39H7 ZCKJ2H7 ZCKJD35H7 ZCKJ41 ZCKJ7H7 ZCKJD35 ZCKJ11H7 ZCKJ1H7 ZCKJ1H29 ZCKJ5H7 ZCKJ5H29 ZCKJ7 ZCKJD31 ZCKJ41H7 ZCKJ5 ZCKJ4H29 ZCKJ6H7 ZCKJD35H29 ZCKJD37H7 ZCKJ8H7 ZCKJ7H29 ZCKJD39H29 ZCKJ4 ZCKJ21H7 ZCKJ11 ZCKJ21H29

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCKJ6
 ZCKJ9H7
 ZCKJ2H29
 ZCKJ9
 ZCKJ4H7
 ZCKJD31H29
 ZCKJD31H7
 ZCKJ2
 ZCKJ11H29
 ZCKJD37H29
 ZCKJ8H29
 ZCKJD39
 ZCKJ21
 ZCKJ1

Movement of operating head	Linear
Type of operator	End plunger spring return metal
Type of approach	Vertical approach, 1 direction

Complementary

Switch actuation	On end
Positive opening	With
Head material	Metal

Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Environmental characteristic	Standard environment

Packing Units

Package 1 Weight	0.142 kg
Package 1 Height	0.400 dm
Package 1 width	0.480 dm
Package 1 Length	0.900 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------