

Contactor, AC-3, 37 kW / 400 V, 1 NO + 1 NC, 110 V AC, 50 Hz, 3-pole, Size S2, screw terminal



|                          |                 |
|--------------------------|-----------------|
| product brand name       | SIRIUS          |
| product designation      | Power contactor |
| product type designation | 3RT2            |

| General technical data                                                                              |        |
|-----------------------------------------------------------------------------------------------------|--------|
| size of contactor                                                                                   | S2     |
| product extension                                                                                   |        |
| <ul style="list-style-type: none"> <li>function module for communication</li> </ul>                 | No     |
| <ul style="list-style-type: none"> <li>auxiliary switch</li> </ul>                                  | Yes    |
| power loss [W] for rated value of the current                                                       |        |
| <ul style="list-style-type: none"> <li>at AC in hot operating state</li> </ul>                      | 17.1 W |
| <ul style="list-style-type: none"> <li>at AC in hot operating state per pole</li> </ul>             | 5.7 W  |
| power loss [W] for rated value of the current without load current share typical                    | 16 W   |
| surge voltage resistance                                                                            |        |
| <ul style="list-style-type: none"> <li>of main circuit rated value</li> </ul>                       | 6 kV   |
| <ul style="list-style-type: none"> <li>of auxiliary circuit rated value</li> </ul>                  | 6 kV   |
| maximum permissible voltage for safe isolation                                                      |        |
| <ul style="list-style-type: none"> <li>between coil and main contacts acc. to EN 60947-1</li> </ul> | 400 V  |

|                                                                                       |                             |
|---------------------------------------------------------------------------------------|-----------------------------|
| <b>protection class IP</b>                                                            |                             |
| • on the front                                                                        | IP20                        |
| • of the terminal                                                                     | IP00                        |
| <b>shock resistance at rectangular impulse</b>                                        |                             |
| • at AC                                                                               | 11.8g / 5 ms, 7.4g / 10 ms  |
| <b>shock resistance with sine pulse</b>                                               |                             |
| • at AC                                                                               | 18.5g / 5 ms, 11.6g / 10 ms |
| <b>mechanical service life (switching cycles)</b>                                     |                             |
| • of contactor typical                                                                | 10 000 000                  |
| • of the contactor with added electronically optimized auxiliary switch block typical | 5 000 000                   |
| • of the contactor with added auxiliary switch block typical                          | 10 000 000                  |
| <b>reference code acc. to IEC 81346-2</b>                                             | Q                           |

|                                                           |                |
|-----------------------------------------------------------|----------------|
| <b>Ambient conditions</b>                                 |                |
| • installation altitude at height above sea level maximum | 2 000 m        |
| <b>ambient temperature</b>                                |                |
| • during operation                                        | -25 ... +60 °C |
| • during storage                                          | -55 ... +80 °C |

|                                                                     |        |
|---------------------------------------------------------------------|--------|
| <b>Main circuit</b>                                                 |        |
| <b>number of poles for main current circuit</b>                     | 3      |
| <b>number of NO contacts for main contacts</b>                      | 3      |
| <b>operating voltage</b>                                            |        |
| • at AC-3 rated value maximum                                       | 690 V  |
| <b>operational current</b>                                          |        |
| • at AC-1 at 400 V<br>— at ambient temperature 40 °C rated value    | 90 A   |
| • at AC-1<br>— up to 690 V at ambient temperature 40 °C rated value | 90 A   |
| — up to 690 V at ambient temperature 60 °C rated value              | 80 A   |
| • at AC-3<br>— at 400 V rated value                                 | 80 A   |
| — at 500 V rated value                                              | 80 A   |
| — at 690 V rated value                                              | 58 A   |
| • at AC-4 at 400 V rated value                                      | 55 A   |
| • at AC-5a up to 690 V rated value                                  | 79.2 A |
| • at AC-5b up to 400 V rated value                                  | 66.4 A |
| • at AC-6a                                                          |        |

|                                                                        |                    |
|------------------------------------------------------------------------|--------------------|
| — up to 230 V for current peak value n=20 rated value                  | 70 A               |
| — up to 400 V for current peak value n=20 rated value                  | 70 A               |
| — up to 500 V for current peak value n=20 rated value                  | 70 A               |
| — up to 690 V for current peak value n=20 rated value                  | 58 A               |
| • at AC-6a                                                             |                    |
| — up to 230 V for current peak value n=30 rated value                  | 46.7 A             |
| — up to 400 V for current peak value n=30 rated value                  | 46.7 A             |
| — up to 500 V for current peak value n=30 rated value                  | 46.7 A             |
| — up to 690 V for current peak value n=30 rated value                  | 46.7 A             |
| <b>minimum cross-section in main circuit</b>                           |                    |
| • at maximum AC-1 rated value                                          | 35 mm <sup>2</sup> |
| <b>operational current for approx. 200000 operating cycles at AC-4</b> |                    |
| • at 400 V rated value                                                 | 30 A               |
| • at 690 V rated value                                                 | 24 A               |
| <b>operational current</b>                                             |                    |
| • at 1 current path at DC-1                                            |                    |
| — at 24 V rated value                                                  | 55 A               |
| — at 110 V rated value                                                 | 4.5 A              |
| — at 220 V rated value                                                 | 1 A                |
| — at 440 V rated value                                                 | 0.4 A              |
| — at 600 V rated value                                                 | 0.25 A             |
| • with 2 current paths in series at DC-1                               |                    |
| — at 24 V rated value                                                  | 55 A               |
| — at 110 V rated value                                                 | 45 A               |
| — at 220 V rated value                                                 | 5 A                |
| — at 440 V rated value                                                 | 1 A                |
| — at 600 V rated value                                                 | 0.8 A              |
| • with 3 current paths in series at DC-1                               |                    |
| — at 24 V rated value                                                  | 55 A               |
| — at 110 V rated value                                                 | 55 A               |
| — at 220 V rated value                                                 | 45 A               |
| — at 440 V rated value                                                 | 2.9 A              |
| — at 600 V rated value                                                 | 1.4 A              |
| <b>operational current</b>                                             |                    |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                       |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• at 1 current path at DC-3 at DC-5 <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul> </li> <li>• with 2 current paths in series at DC-3 at DC-5 <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul> </li> <li>• with 3 current paths in series at DC-3 at DC-5 <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul> </li> </ul> | 35 A<br>2.5 A<br>1 A<br>0.1 A<br>0.06 A<br><br>55 A<br>25 A<br>5 A<br>0.27 A<br>0.16 A<br><br>55 A<br>55 A<br>25 A<br>0.6 A<br>0.35 A |
| <b>operating power</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                                                                       |
| <ul style="list-style-type: none"> <li>• at AC-2 at 400 V rated value</li> <li>• at AC-3 <ul style="list-style-type: none"> <li>— at 230 V rated value</li> <li>— at 400 V rated value</li> <li>— at 500 V rated value</li> <li>— at 690 V rated value</li> </ul> </li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 37 kW<br><br>22 kW<br>37 kW<br>37 kW<br>45 kW                                                                                         |
| <b>operating power for approx. 200000 operating cycles at AC-4</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                                                                                       |
| <ul style="list-style-type: none"> <li>• at 400 V rated value</li> <li>• at 690 V rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 15.8 kW<br>21.8 kW                                                                                                                    |
| <b>operating apparent power at AC-6a</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                       |
| <ul style="list-style-type: none"> <li>• up to 230 V for current peak value n=20 rated value</li> <li>• up to 400 V for current peak value n=20 rated value</li> <li>• up to 500 V for current peak value n=20 rated value</li> <li>• up to 690 V for current peak value n=20 rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 27.8 kV·A<br>48.4 kV·A<br>60.6 kV·A<br>69.3 kV·A                                                                                      |
| <b>operating apparent power at AC-6a</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                       |
| <ul style="list-style-type: none"> <li>• up to 230 V for current peak value n=30 rated value</li> <li>• up to 400 V for current peak value n=30 rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 18.6 kV·A<br>32.3 kV·A                                                                                                                |

|                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                                                                                                                                                                                 |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• up to 500 V for current peak value n=30 rated value</li> <li>• up to 690 V for current peak value n=30 rated value</li> </ul>                                                                                                                                                                                                                                                          | 40.4 kV·A<br><br>55.8 kV·A                                                                                                                                                                                                                                                                                                      |
| <b>short-time withstand current in cold operating state up to 40 °C</b> <ul style="list-style-type: none"> <li>• limited to 1 s switching at zero current maximum</li> <li>• limited to 5 s switching at zero current maximum</li> <li>• limited to 10 s switching at zero current maximum</li> <li>• limited to 30 s switching at zero current maximum</li> <li>• limited to 60 s switching at zero current maximum</li> </ul> | 1 298 A; Use minimum cross-section acc. to AC-1 rated value<br><br>898 A; Use minimum cross-section acc. to AC-1 rated value<br><br>640 A; Use minimum cross-section acc. to AC-1 rated value<br><br>414 A; Use minimum cross-section acc. to AC-1 rated value<br><br>333 A; Use minimum cross-section acc. to AC-1 rated value |
| <b>no-load switching frequency</b> <ul style="list-style-type: none"> <li>• at AC</li> </ul>                                                                                                                                                                                                                                                                                                                                    | 5 000 1/h                                                                                                                                                                                                                                                                                                                       |
| <b>operating frequency</b> <ul style="list-style-type: none"> <li>• at AC-1 maximum</li> <li>• at AC-2 maximum</li> <li>• at AC-3 maximum</li> <li>• at AC-4 maximum</li> </ul>                                                                                                                                                                                                                                                 | 700 1/h<br>350 1/h<br>500 1/h<br>150 1/h                                                                                                                                                                                                                                                                                        |

| Control circuit/ Control                                                                                                                           |              |
|----------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
| <b>type of voltage of the control supply voltage</b>                                                                                               | AC           |
| <b>control supply voltage at AC</b> <ul style="list-style-type: none"> <li>• at 50 Hz rated value</li> </ul>                                       | 110 V        |
| <b>operating range factor control supply voltage rated value of magnet coil at AC</b> <ul style="list-style-type: none"> <li>• at 50 Hz</li> </ul> | 0.8 ... 1.1  |
| <b>apparent pick-up power of magnet coil at AC</b> <ul style="list-style-type: none"> <li>• at 50 Hz</li> </ul>                                    | 190 V·A      |
| <b>inductive power factor with closing power of the coil</b> <ul style="list-style-type: none"> <li>• at 50 Hz</li> </ul>                          | 0.72         |
| <b>apparent holding power of magnet coil at AC</b> <ul style="list-style-type: none"> <li>• at 50 Hz</li> </ul>                                    | 16 V·A       |
| <b>inductive power factor with the holding power of the coil</b> <ul style="list-style-type: none"> <li>• at 50 Hz</li> </ul>                      | 0.37         |
| <b>closing delay</b> <ul style="list-style-type: none"> <li>• at AC</li> </ul>                                                                     | 10 ... 80 ms |
| <b>opening delay</b> <ul style="list-style-type: none"> <li>• at AC</li> </ul>                                                                     | 10 ... 18 ms |

|                                                     |                                                 |
|-----------------------------------------------------|-------------------------------------------------|
| arcing time                                         | 10 ... 20 ms                                    |
| control version of the switch operating mechanism   | Standard A1 - A2                                |
| <b>Auxiliary circuit</b>                            |                                                 |
| <b>number of NC contacts for auxiliary contacts</b> |                                                 |
| • instantaneous contact                             | 1                                               |
| <b>number of NO contacts for auxiliary contacts</b> |                                                 |
| • instantaneous contact                             | 1                                               |
| operational current at AC-12 maximum                | 10 A                                            |
| <b>operational current at AC-15</b>                 |                                                 |
| • at 230 V rated value                              | 10 A                                            |
| • at 400 V rated value                              | 3 A                                             |
| • at 500 V rated value                              | 2 A                                             |
| • at 690 V rated value                              | 1 A                                             |
| <b>operational current at DC-12</b>                 |                                                 |
| • at 24 V rated value                               | 10 A                                            |
| • at 48 V rated value                               | 6 A                                             |
| • at 60 V rated value                               | 6 A                                             |
| • at 110 V rated value                              | 3 A                                             |
| • at 125 V rated value                              | 2 A                                             |
| • at 220 V rated value                              | 1 A                                             |
| • at 600 V rated value                              | 0.15 A                                          |
| <b>operational current at DC-13</b>                 |                                                 |
| • at 24 V rated value                               | 10 A                                            |
| • at 48 V rated value                               | 2 A                                             |
| • at 60 V rated value                               | 2 A                                             |
| • at 110 V rated value                              | 1 A                                             |
| • at 125 V rated value                              | 0.9 A                                           |
| • at 220 V rated value                              | 0.3 A                                           |
| • at 600 V rated value                              | 0.1 A                                           |
| <b>contact reliability of auxiliary contacts</b>    | 1 faulty switching per 100 million (17 V, 1 mA) |
| <b>UL/CSA ratings</b>                               |                                                 |
| <b>full-load current (FLA) for 3-phase AC motor</b> |                                                 |
| • at 480 V rated value                              | 65 A                                            |
| • at 600 V rated value                              | 62 A                                            |
| <b>yielded mechanical performance [hp]</b>          |                                                 |
| • for single-phase AC motor                         |                                                 |
| — at 110/120 V rated value                          | 5 hp                                            |
| — at 230 V rated value                              | 15 hp                                           |
| • for 3-phase AC motor                              |                                                 |
| — at 200/208 V rated value                          | 20 hp                                           |
| — at 220/230 V rated value                          | 25 hp                                           |

|                                                             |             |
|-------------------------------------------------------------|-------------|
| — at 460/480 V rated value                                  | 50 hp       |
| — at 575/600 V rated value                                  | 60 hp       |
| <b>contact rating of auxiliary contacts according to UL</b> | A600 / P600 |

## Short-circuit protection

|                                                                                                                                                                                                                                                                                                                         |                                                                                                                                                                                                  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>design of the fuse link</b>                                                                                                                                                                                                                                                                                          |                                                                                                                                                                                                  |
| <ul style="list-style-type: none"> <li>for short-circuit protection of the main circuit           <ul style="list-style-type: none"> <li>with type of coordination 1 required</li> <li>with type of assignment 2 required</li> </ul> </li> <li>for short-circuit protection of the auxiliary switch required</li> </ul> | <p>gG: 250 A (690 V, 100 kA), aM: 160 A (690 V, 100 kA), BS88: 200 A (415 V, 80 kA)</p> <p>gG: 160A (690V,100kA), aM: 80A (690V,100kA), BS88: 125A (415V,80kA)</p> <p>gG: 10 A (500 V, 1 kA)</p> |

## Installation/ mounting/ dimensions

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                                                                                          |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>mounting position</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | +/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface                     |
| <b>fastening method</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 60715                                                                   |
| <ul style="list-style-type: none"> <li>side-by-side mounting</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Yes                                                                                                                                                      |
| <b>height</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 114 mm                                                                                                                                                   |
| <b>width</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 55 mm                                                                                                                                                    |
| <b>depth</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 130 mm                                                                                                                                                   |
| <b>required spacing</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                                          |
| <ul style="list-style-type: none"> <li>with side-by-side mounting           <ul style="list-style-type: none"> <li>forwards</li> <li>upwards</li> <li>downwards</li> <li>at the side</li> </ul> </li> <li>for grounded parts           <ul style="list-style-type: none"> <li>forwards</li> <li>upwards</li> <li>at the side</li> <li>downwards</li> </ul> </li> <li>for live parts           <ul style="list-style-type: none"> <li>forwards</li> <li>upwards</li> <li>downwards</li> <li>at the side</li> </ul> </li> </ul> | <p>10 mm</p> <p>10 mm</p> <p>10 mm</p> <p>0 mm</p> <p>10 mm</p> <p>10 mm</p> <p>6 mm</p> <p>10 mm</p> <p>10 mm</p> <p>10 mm</p> <p>10 mm</p> <p>6 mm</p> |

## Connections/ Terminals

|                                                                                                                       |                                                         |
|-----------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------|
| <b>type of electrical connection</b>                                                                                  |                                                         |
| <ul style="list-style-type: none"> <li>for main current circuit</li> <li>for auxiliary and control circuit</li> </ul> | <p>screw-type terminals</p> <p>screw-type terminals</p> |

|                                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                                  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• at contactor for auxiliary contacts</li> <li>• of magnet coil</li> </ul>                                                                                                                                                                                                                               | Screw-type terminals<br>Screw-type terminals                                                                                                                                     |
| <b>type of connectable conductor cross-sections</b> <ul style="list-style-type: none"> <li>• for main contacts <ul style="list-style-type: none"> <li>— solid or stranded</li> <li>— finely stranded with core end processing</li> </ul> </li> <li>• at AWG cables for main contacts</li> </ul>                                                 | 2x (1 ... 35 mm <sup>2</sup> ), 1x (1 ... 50 mm <sup>2</sup> )<br>2x (1 ... 25 mm <sup>2</sup> ), 1x (1 ... 35 mm <sup>2</sup> )<br>2x (18 ... 2), 1x (18 ... 1)                 |
| <b>connectable conductor cross-section for main contacts</b> <ul style="list-style-type: none"> <li>• finely stranded with core end processing</li> </ul>                                                                                                                                                                                       | 1 ... 35 mm <sup>2</sup>                                                                                                                                                         |
| <b>connectable conductor cross-section for auxiliary contacts</b> <ul style="list-style-type: none"> <li>• solid or stranded</li> <li>• finely stranded with core end processing</li> </ul>                                                                                                                                                     | 0.5 ... 2.5 mm <sup>2</sup><br>0.5 ... 2.5 mm <sup>2</sup>                                                                                                                       |
| <ul style="list-style-type: none"> <li>• type of connectable conductor cross-sections for auxiliary contacts <ul style="list-style-type: none"> <li>— solid or stranded</li> <li>— finely stranded with core end processing</li> </ul> </li> <li>• type of connectable conductor cross-sections at AWG cables for auxiliary contacts</li> </ul> | 2x (0,5 ... 1,5 mm <sup>2</sup> ), 2x (0,75 ... 2,5 mm <sup>2</sup> )<br>2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> )<br>2x (20 ... 16), 2x (18 ... 14) |
| <b>AWG number as coded connectable conductor cross section</b> <ul style="list-style-type: none"> <li>• for main contacts</li> <li>• for auxiliary contacts</li> </ul>                                                                                                                                                                          | 18 ... 1<br>20 ... 14                                                                                                                                                            |

#### Safety related data

|                                                                                                                                                                                     |                                                                  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------|
| <b>B10 value</b> <ul style="list-style-type: none"> <li>• with high demand rate acc. to SN 31920</li> </ul>                                                                         | 1 000 000                                                        |
| <b>proportion of dangerous failures</b> <ul style="list-style-type: none"> <li>• with low demand rate acc. to SN 31920</li> <li>• with high demand rate acc. to SN 31920</li> </ul> | 40 %<br>73 %                                                     |
| <b>failure rate [FIT]</b> <ul style="list-style-type: none"> <li>• with low demand rate acc. to SN 31920</li> </ul>                                                                 | 100 FIT                                                          |
| <b>product function</b> <ul style="list-style-type: none"> <li>• mirror contact acc. to IEC 60947-4-1</li> <li>• positively driven operation acc. to IEC 60947-5-1</li> </ul>       | Yes<br>No                                                        |
| <b>T1 value for proof test interval or service life acc. to IEC 61508</b>                                                                                                           | 20 y                                                             |
| <b>touch protection against electrical shock</b>                                                                                                                                    | finger-safe when touched vertically from front acc. to IEC 60529 |
| suitability for use safety-related switching OFF                                                                                                                                    | Yes                                                              |

#### Certificates/ approvals

| General Product Approval | EMC |
|--------------------------|-----|
|--------------------------|-----|



[KC](#)



| Declaration of Conformity | Test Certificates | Marine / Shipping |
|---------------------------|-------------------|-------------------|
|---------------------------|-------------------|-------------------|



[Miscellaneous](#)

[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)



| Marine / Shipping | other |
|-------------------|-------|
|-------------------|-------|



[Confirmation](#)

#### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<https://www.siemens.com/ic10>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2038-1AF00>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2038-1AF00>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2038-1AF00>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**




[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RT2038-1AF00&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2038-1AF00&lang=en)


**Characteristic: Tripping characteristics,  $I^2t$ , Let-through current**

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2038-1AF00/char>

**Further characteristics (e.g. electrical endurance, switching frequency)**

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RT2038-1AF00&objecttype=14&gridview=view1>





last modified:

11/19/2020