

[NEOZED-Sicherungseinsatz], D01, 4 A, [gG], Un AC: 400 V, Un DC: 250 V, [mit verzinnten Kontaktkappen]



Model	
product brand name	SETRON
product designation	NEOZED fuse link
design of the product	With tin-coated contact caps
product variations	Pack of 10
design of the fuse link	NEOZED fuse link
General technical data	
size of fuse system / acc. to DIN EN 60269-1	D01
operating class of the fuse link	gG
Supply voltage	
operational current / at AC / rated value	4 A
supply voltage	
• at AC / rated value	400 V
• at DC	250 V
operating voltage / rated value	400 V
protection class IP	IP20, with connected conductors
switching capacity current / acc. to IEC 60947-2 / rated value	50 kA

Dissipation

power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	1.3 W
---	-------

Main circuit

operational current / rated value	4 A
-----------------------------------	-----

Appearance

color coding of the fuse link	Brown
breaking capacity maximum short-circuit current (Icu) / at AC / rated value	50 kA

Mechanical Design

mounting position	Any, preferably vertical
net weight	7 g
ambient temperature • minimum • maximum	-5 °C 40 °C
environmental category	Up to 45°C at 95 % rel. humidity

Certificates

reference code	
• acc. to DIN EN 61346-2 • acc. to IEC 81346-2	F F

General Product Approval

Declaration of Conformity

Test Certificates



ÖVE



VDE



EG-Konf.

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

[Miscellaneous](#)

other

[Environmental Conformations](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SE2304>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SE2304>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SE2304

