

# Dustproof

## Water, Vapor, Dust, Proof.

Our IP65 LED dustproof is composed of a UV stabilized polycarbonate body which gives excellent protection from long-term degradation from sunlight as well as an IK08/5J optic impact rating. This stout luminaire is fully serviceable and comes with an ambient temperature rating of up to 35 degrees Celsius.



### SPEC sheet

## 2 Foot 4 Foot 5 Foot

Raw Lumen:	2913 lm	3964 lm	5480 lm	7660 lm	6800 lm	9095 lm
Effective Lumen:	2700 lm	3675 lm	5080 lm	6870 lm	6304 lm	8431 lm
240V:	<b>20W</b>	<b>29W</b>	<b>38W</b>	<b>54W</b>	<b>46W</b>	<b>66W</b>
Raw Efficacy:	142 lm/w	139 lm/w	144 lm/w	142 lm/w	148 lm/w	138 lm/w
Effective Efficacy:	134 lm/w	128 lm/w	134 lm/w	127 lm/w	136 lm/w	130 lm/w
L90 B10 @ 25°:	>54000Hrs		>54000Hrs		>54000Hrs	
L80 B10 @ 35°:	>50000 Hrs		>50000 Hrs		>50000 Hrs	
Fitting Length:	<b>620mm</b>		<b>1250mm</b>		<b>1540mm</b>	

See our full brochure for other sizes and specifications.

### KEY FEATURES

#### 3 SIZE OPTIONS


- Dustproof 2 Foot
- Dustproof 4 Foot
- Dustproof 5 Foot

#### DIFFUSER

- Impact rating IK08/5J

#### TEMPERATURE

- Ambient room temperature -5°C to +35°C.



**Optional:**  
Bluetooth, Wifi,  
Dali & Bi Level



**kV Protection:**  
1kV, 2kV on request



**Colour Temp:**  
5600K  
CR>80 R9>13



**Indoor/Outdoor**




**Impact Resistance:**  
IK08/5J



**Housing Diffuser:**  
Polycarbonate

### Dustproof Distribution



BETTER LIGHT THROUGH RESEARCH

sales@energywise.co.za | www.energywise.co.za

T: +27 31 764 2345 / +27 87 941 0012

Physical address: Unit 5 Edstan Business Park, 2 Ibhubs Road, Riverhorse Valley, Durban, South Africa, 4017

Postal address: PO Box 1166, Kloof, South Africa, 3640

