



# MOISTURE PROOF (WIRED FOR LED)

## FEATURES:

- IP 65 Dust and Moisture Proof fitting.
- Suitable for Underground car parks, cold rooms, freezer rooms (-20 degrees Celsius)
- Food preparation/packaging rooms.
- Wired for LED T8 Configurations - L/N Live Neutral Connection Single-Side
- Full Polycarbonate, Stainless Steel Clips, Fire retardant.

**BENEFITS:** IEC, NRCS approved

**DAYLIGHT**  
LIGHTING

PREMIUM LIGHTING FOR HOUSEHOLD, INDUSTRIAL AND COMMERCIAL APPLICATIONS

## T8 LED Technical Data

Product Code	Lamp Configuration	Clips	Input Voltage	Dimensions L x B x H	PF	IP Rating
01x18w-led	1*2ft LED Tube	Stainless Steel	220-240	660mm*70mm*61mm	LED Tube Specific	65
01x36w-led	1*4ft LED Tube	Stainless Steel	220-240	1260mm*70mm*61mm	LED Tube Specific	65
01x58w-led	1*5ft LED Tube	Stainless Steel	220-240	1562mm*70mm*61mm	LED Tube Specific	65
02x18w-led	2*2ft LED Tube	Stainless Steel	220-240	660mm*107mm*61mm	LED Tube Specific	65
02x36w-led	2*4ft LED Tube	Stainless Steel	220-240	1260mm*107mm*61mm	LED Tube Specific	65
02x58w-led	2*5ft LED Tube	Stainless Steel	220-240	1562mm*107mm*61mm	LED Tube Specific	65

All LED fittings wired Live - Neutral, one end only With 2amp replacable fuse ( As per SABS standards)

**DAYLIGHT**  
LIGHTING

PREMIUM LIGHTING FOR HOUSEHOLD,  
INDUSTRIAL & COMMERCIAL APPLICATIONS

Daylight Lighting (Pty) Ltd  
Distribution throughout South Africa and Africa

Offices in: Port Elizabeth (Head Office), Cape Town, Johannesburg, Durban and Bloemfontein  
Tel: +27 (0) 41 484 3330 | Web: [www.daylightlighting.co.za](http://www.daylightlighting.co.za) | Email: [sales@daylightlighting.co.za](mailto:sales@daylightlighting.co.za)