

LED UFO HIGHBAY



150W LED UFO SPECIFICATION

S/CAS-HB-150-5K

Luminaire Wattage	150W
Effective Luminous Flux	24 000 Lumens
Efficacy	160 lm/W
Correlated Colour Temperature (CCT)	5000K
Colour Rendering Index (CRI)	+80
Beam Angle	90° Standard *
Power Factor	0.92
Input Voltage	220-240 Vac, 50/60Hz
Surge Protection	10kV
Operating Temperature	-30°C to + 50°C
IP Rating	65
Lifespan of LED @Ta=25°C (hours)	L80B10-73000 Hours
Warranty	5 Years
Materials & Finish	Aluminum Alloy Polycarbonate Optical Lens Black Powder Coating (RAL9017)
Gross Weight	2.2kg
Certification	CE, RoHs, CB. SAA and C-Tick
Mounting type	Suspension/Ceiling Mount

200W LED UFO SPECIFICATION

S/CAS-HB-200-5K

Luminaire Wattage	200W
Effective Luminous Flux	32 000 Lumens
Efficacy	160 lm/W
Correlated Colour Temperature (CCT)	5000K
Colour Rendering Index (CRI)	+80
Beam Angle	90° Standard *
Power Factor	0.92
Input Voltage	220-240 Vac, 50/60Hz
Surge Protection	10kV
Operating Temperature	-30°C to + 50C
IP Rating	65
Lifespan of LED @Ta=25°C (hours)	L80B10-73000 Hours
Warranty	5 Years
Materials & Finish	Aluminium Alloy Polycarbonate Optical Lens Black Powder Coating (RAL9017)
Gross Weight	2.9kg
Certification	CE, RoHs, CB. SAA and C-Tick
Mounting type	Suspension/Ceiling Mount

Note: Microwave sensor, mounting bracket and lenses * (60° & 120°) available as accessories